

II. Dimensions of works:

(a) Height of dam, 15 feet; length of dam at top, 100 feet; length of dam at bottom, 90 feet; material used in construction (wood, earth, stone or concrete) concrete

(b) Capacity of reservoir _____ acre-feet.

(c) Size of headgate—width, 4 feet; height, 15 feet.

(d) Ditch (flume or pipe)—width at bottom, 4 feet; width at water line, 6 feet; depth of water, _____ feet. Average grade per mile is 10 feet. Length of ditch is 1 miles, and crosses the following

quarter sections: N.E. 1/4 Sec. 9; S.E. 1/4 Sec. 9; N.E. 1/4 Sec. 16; S.E. 1/4 Sec. 16; S.W. 1/4 Sec. 16; T. 14 S. R. 50 E. M. D. M. on which used for irrigation and E 1/2 Sec. 4. to Rhyolite which is the point of intended use.

APPROVAL OF STATE ENGINEER

The number of this permit is 221.

Date of receipt of first application Oct. 6, 1906.

Return to applicant for correction _____ 190 .

Corrected application received _____ 190 .

Last notice published _____ 190 .

Recorded in Book B, page 221.

✓ Approved Jan. 22, 1907.

This is to certify that I have examined the within application for a permit to appropriate the public waters of the State of Nevada, and hereby grant the same, subject to the following limitations and conditions:

The amount of water to be appropriated not more than five cubic feet per second.

The construction of the within described works to be commenced not later than

May 1, 1907

One-fifth of the work above specified to be completed on or before Oct. 1, 1907.

The whole of said work to be completed on or before Jan. 1, 1909

The time for the proof of beneficial use of water appropriated in accordance herewith, to extend to Jan. 1, 1910

Witness my hand this twenty second day of January, 1907.

Henry J. Shuttell

State Engineer.

REMARKS

(This space not to be written in by applicants.)

Map Filed July - 19 - 07
Proof of Beneficial Use - FILED NOV 22 1909

Cancelled Jan. 9, 1924 because of failure of applicant to comply with provisions of permit

Robert A. Allen

State Engineer