1468 ASSIGNED

No. 1468

APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Nevada

FILED OCT 20 1909

1. Date of receipt of Application
2. Name of applicant Abramo Arigoni

Postoffice address: Troy

County Nye. Nevada

I. If applicant is a corporation, give

(a) Date and place of corporation

(b) The amount of capital stock

(c) The amount paid in

(d) The names and addresses of Directors

3. The quantity of water claimed is (2 1/4) Two and one fourth cubic feet per second.
4. Source of water supply Burnt Coral Spgs. & Oxhame Spring.
5. Location of point of diversion Probably in Sec 25 - T. 5 N R 56 E. By short lateral ditches from original channel below Oxhame Spring.

I. Irrigation and domestic use:

(a) Number of acres to be irrigated Eighty to one hundred acres.

(b) In the following legal subdivisions

(A list of lands to be irrigated may be appended as a part of this application.)

The north half of the north east quarter of Section 25. The south west quarter of the south east quarter, and the south east quarter of the south west quarter of Section 24, 160 acres, all in Township No. 5 North Range 56 East of Mt Diablo Base and Meridian.

II. Mining, power, manufacturing or transportation purposes:

(a) To be used for

(b) Amount of power to be generated horse power.

(c) At what point

(d) Is water to be returned to stream, ("yes" or "no") No.

(e) If "yes" at what point

7. Estimated cost of works The reservoir dam and lateral ditches will cost $1000.00
8. Description of works for diversion:

I. Kind of works (reservoir, dam, ditch, flume, pipes or otherwise) Masonry Dam. Ditches Etc.

The reservoir dam is 24 ft long on base 26 ft long at crest, 10 ft thick at base, 4 ft thick at crest, built of subble masonry laid up in lime mortar.

Cash. 25.00
Notice to Tonabah Box

ASSIGNED 1468

II. Dimensions of works:

(a) Height of dam, 25 feet; length of dam at top, 36 feet; length of dam at bottom, 24 feet; material used in construction (wood, earth, stone or concrete) Rubble stone masonry laid up in lime mortar, built on rock in place foundation

(b) Capacity of reservoir Twenty acre-feet.

(c) Size of headgate—width, one feet; height, in diameter feet.

(d) Ditch (flume or pipe)—width at bottom, _____ feet width at water line, _____ feet; depth of water, _____ feet. Average grade per mile is _____ feet. Length of ditch is _____ miles, and crosses the following quarter sections: The head gate will discharge in original channel

to _____ which is the point of intended use.

Abramo Arizoni
applicant

APPROVAL OF STATE ENGINEER

The number of this permit is 1468.

Date of receipt of first application October 20th 1909.

Return to applicant for correction _____ 190__.

Corrected application received _____ 190__.

Last notice published Nov - 12 1909. FILED NOV 15 1909

Recorded in Book H., page 1468

Approved, FEB 17 1911 190__.

This is to certify that I have examined the within application for a permit to appropriate the public waters of the State of Nevada, and hereby grant the same, subject to the following limitations and conditions:

The amount of water to be appropriated not more than One cubic feet per second.

The construction of the within described works to be commenced not later than May 15th 1911

One-fifth of the work above specified to be completed on or before January 1st 1912

The whole of said work to be completed on or before January 1st 1913

The time for the proof of beneficial use of water appropriated in accordance herewith, to extend to September 1st 1913

Witness my hand this Seventeenth day of February, 1911

Emmet D Boyle
State Engineer.

REMARKS

This space not to be written in by applicant.

Proof of labor filed July - 5 - 1911
Map - - - - " Aug - 5 - 1910

Proof of beneficial use filed SEP - 2 1913
Cert. issued June 20, 1914.

See 1467

Compared