

APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date of filing in State Engineer's Office NOV 26 1979

Returned to applicant for correction

Corrected application filed

Map filed NOV 26 1979 under 39831

The applicant Patrick Development Company

Post Office Box 3536, of Reno

Street and No. or P.O. Box No. City or Town

Nevada (89505), hereby make application for permission to appropriate the public

State and Zip Code No.

waters of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorporation; if a copartnership or association, give names of members.)

1. The source of the proposed appropriation is Underground Well No. 7 Name of stream, lake or other source.

2. The amount of water applied for is 1.0 second-feet One second-foot equals 448.83 gals. per min.

(a) If stored in reservoir give number of acre-feet acre-feet

3. The water to be used for Quasi-Municipal and Domestic Irrigation, power, mining, manufacturing, domestic, or other use. Must limit to one use.

4. If use is for:

(a) Irrigation (state number of acres to be irrigated)

(b) Stockwater (state number and kinds of animals to be watered)

(c) Other use (describe fully under "No. 12. Remarks")

(d) Power:

(1) Horsepower developed

(2) Point of return of water to stream

5. The water is to be diverted from its source at the following point: SW 1/4 SW 1/4, Section 29, T20N, R22E, M.D.B.&M., or at a point from which the E 1/4 corner of said Section 29 bears, N 58° 30' E 4,880 feet Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land, it should be stated.

6. Place of use Section 21, NE 1/4, NW 1/4, SW 1/4 Section 29, T20N, R22E, M.D.B.&M. Describe by legal subdivision, if on unsurveyed land it should be so stated.

7. Use will begin about January 1 and end about December 31, of each year. Month and Day

8. Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and specifications of your diversion or storage works.) Drill well, install pump and motor, transmission and distribution system and storage tank for complete community water system. State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

- 9. Estimated cost of works..... \$900,000
- 10. Estimated time required to construct works... Three Years
- 11. Estimated time required to complete the application to beneficial use..... Seven Years
- 12. Remarks: For use other than irrigation or stock watering, state number and type of units to be served or annual consumptive use.

This application is to serve approximately 1,300 additional residential units under a planned unit development with a community water system.

This water will be commingled with water from Underground Wells 5 and 6, Permits 35935, 35936, 35937 and 35938. The total for all applications is 3,000 units.

Applicant..... Patrick Development Company

By..... s/Richard W. Arden
Richard W. Arden, Agent
950 Industrial Way
Sparks, Nevada (89431)

Compared..... ha/ ga js/bc

APPROVAL OF STATE ENGINEER

This is to certify that I have examined the foregoing application, and do hereby grant the same, subject to the following limitations and conditions:

This permit is issued subject to existing rights. It is understood that the amount of water herein granted is only a temporary allowance and that the final water right obtained under this permit will be dependent upon the amount of water actually placed to beneficial use. It is also understood that this right must allow for a reasonable lowering of the static water level. This well shall be equipped with a two (2) inch opening for measuring depth to water. If the well is flowing, a valve must be installed and maintained to prevent waste. A totalizing meter must be installed and maintained in the discharge pipeline near the point of diversion and accurate measurements must be kept of water placed to beneficial use. The totalizing meter must be installed before any use of water begins, or before the Proof of Completion of Work is filed. This source is located within an area designated by the State Engineer, pursuant to NRS 534.030. The State retains the right to regulate the use of the water herein granted at any and all times.

This Permit does not extend the permittee the right of ingress and egress on public, private or corporate lands.

The issuance of this permit does not waive the requirements that the permit holder obtain other permits from State, Federal and local agencies.

(CONTINUED ON PAGE 2)

The amount of water to be appropriated shall be limited to the amount which can be applied to beneficial use, and not to exceed 1.0 cubic feet per second, but not to exceed 235.9 million gallons annually.

Actual construction work shall begin on or before.....

Proof of commencement of work shall be filed before.....

Work must be prosecuted with reasonable diligence and be completed on or before March 26, 1986

Proof of completion of work shall be filed before April 26, 1986

Application of water to beneficial use shall be made on or before March 26, 1988

Proof of the application of water to beneficial use shall be filed on or before April 26, 1988

Map in support of proof of beneficial use shall be filed on or before April 26, 1988

Commencement of work filed..... IN TESTIMONY WHEREOF, I..... PETER G. MORROS
Completion of work filed..... State Engineer of Nevada, have hereunto set my hand and the seal of
Proof of beneficial use filed..... my office, this 8th day of October

Cultural map filed.....
Certificate No. JAN 08 1990 issued..... BECAUSE OF FAILURE
CANCELED

A.D. 1985

[Signature]
State Engineer

OF APPLICANT TO COMPLY WITH THE PROVISIONS OF PERMIT
18 (Rev.)
[Signature]
STATE ENGINEER

(PERMIT TERMS CONTINUED)

The total combined duty of water under Permits 35935, 35936, 35937, 35938, 39831, 39832 and 39833 shall not exceed 620.5 million gallons annually.

At least two ground water monitoring wells are to be installed within the place of use at locations satisfactory to the State Engineer before any diversion of groundwater from the production well takes place. The monitoring wells must be suitably cased, perforated, sealed and capped, and must penetrate at least 75 feet below the water table.

