

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 8309  
 Rec. Jan 8 1965  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner Lester Matthews Driller Darell Lee  
 Address Panaca, Nevada Address Panaca, Nevada Lic. No. 30  
 Location of well: S.W. 1/4 S.W. 1/4 Sec. 5, T. 2 N/S, R. 68 E, in Lincoln County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 98'  
 Size of drilled hole 14" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 14" 74'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 39'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well December 3, 1964 Date of completion of well December 11, 1964  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	38	38	sandy silt
38	65	27	gravel
65	74	9	gravel in clay
74	98	24	Panaca bed

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 38' to 65' ft.

Other aquifers \_\_\_\_\_

---

First water at 39' feet.

---

Casing perforated

from 39' to 74' ft.

---

Size of perforations

1/8 x 1 1/2"

