

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4288  
 Rec. Sept 29 1958  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Farrell Ansholev Driller Paul Free  
 Address 1616 Nevada Address Picacho, Nevada Lic. No. 30  
 Location of well: NW 1/4, NW 1/4, Sec. 32, T. 6 N/S, R. 4 E, in Lincoln County  
 or across the road from the Ansholev home, near the Adams Highway, 11/2 miles north  
 Water will be used for Domestic Total depth of well 40'  
 Size of drilled hole 8" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 12 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" 32'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 20'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well August 20, 1958 Date of completion of well August 22, 1958  
 Type of well rig Common Drill

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	sand and gravel
20	40	20	sand and gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 20 to 40 ft.

Other aquifers \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

First water at 20 feet.

Casing perforated  
 from 22 to 40 ft.

Size of perforations  
1/4" X 12"

