WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 261
Rec. 11/24 1947
Well No.
Permit No.
Do not fill in

Owner: John E. Jackson — Driller: J.C. Farettto & Son

Address: P.O. Box 2247 Reno, Nev. — Address: 736 Humboldt St. Reno, Nev. Lic. No. 2

Location of well: N.W.¼N.W.¼ Sec. 20, T. 18 N/S, R 20 E, in Truckee Meadows, Washoe County

or 7 miles south on Reno-Carson Highway, turn west ½ mile on Zolezzi lane.

Water will be used for: Domestic & irrigation — Total depth of well: 95 ft.

Size of drilled hole: 14 inch hole. — Weight of casing per linear foot:

Thickness of casing: ¼ inch — Temp. of water: 57°

Diameter and length of casing: 14 inch O.D. 12 ft. lengths.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 61 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: October 30, 1947 — Date of completion of well: November 3, 1947.

Type of well rig: Cable Tool Rig. 500 ft. Keystone Tye Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
80	85	5	Fine sand & silt.
85	86	1	Clean sand.
86	90	4	Fine sand, silt & clay.
90	95	5	Fine sand, with yellow clay.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 85 to 86 ft.

Other aquifers: 86 to 95 ft.
80 to 85 ft.

First water at 65 feet.

Casing perforated
from 56 to 91 ft.

Size of perforations
about ⅛" x 3"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14" O.D.	78'-11"	98'-04"	36'-00"	Owner installed no well ring or shoe on casing. Bottom of casing dented in slightly enough to stick the well bit. Is O.K. for a 10" casing reduction with a starter pipe with well ring built on.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

This well is a round concrete hole 3'-04" in diamter and 65 ft. deep dug by hand. The owner sunk a 14 inch O.D. pipe in this shaft to a depth of about 14 ft. with a suction tye bailer. The top of the casing when we started to drill was 42'-11" from the ground level. We left the casing at 55'-04" from the top of the ground.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J.C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated November 4, 1947

(Not to be filled in by Driller)