

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA



Log No. 367  
 Rec. 194  
 Well No. 34384  
 Permit No. 10940 11706  
 Do not fill in

*Sent to State Eng.*

Owner Elda, J.T. & W.O. Gilcrease Driller T.B. Miller

Address Las Vegas, Nevada Address Box 248 Pitman, Nev. Lic. No. 40

Location of well: SE 1/4 SW 1/4 Sec 9, T. 19 N/S, R. 60 E, in Clark Count.

Water will be used for Irrigation & Domestic Total depth of well 556 ft

Size of drilled hole 20" Weight of casing per linear foot 16"-36# 10" -36#

Thickness of casing 16" 1/2" 10" 1/2" Temp. of water 69

Diameter and length of casing 268' of 16" I.D. 380' of 10' I.D.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 3.42 c.f.s. Unable to get pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works Flange for valve (no valve to date)  
 (Type and size of valve, etc.)

Date of commencement of well Oct 12, 1947 Date of completion of well Jan, 15, 1948

Type of well rig Armstrong 50

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
			Formations same as on log filed Sept. 16, 1946 Original depth of well 612'	Chief aquifer (water-bearing formation) from <u>512</u> to <u>530</u> ft. Other aquifers <u>325 to 330</u> <u>351 to 365</u>
			<i>By Charles C. Wells Note.</i> 5/1/50 - 130' of 13" O.D. pipe was welded to 10" pipe and lowered in well, which puts bottom of 10" at 510'. The 13" had large perforation also in pipe.	First water at <u>91</u> feet. 10" casing perforated from <u>12</u> to <u>390</u> ft. Size of perforations <u>1/2" by 4" 12" apart</u>

