X

Log No. 494 ✓
Rec. 5/13 1948
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner: MR & MRS DORFENDORFER. Driller: MEL MEYER.

Address: TRUCKEE RD. SPARKS NEV. Address: RT 1 BOX 10 RENO Lic. No. 3

Location of well: ¼ ¼ Sec. 34, T. 20 N/S, R 20 E, in CLASHOE County

or PART IN SHOP.

Water will be used for HOUSE HOLD Total depth of well 39'

Size of drilled hole 6" Weight of casing per linear foot 20#

Thickness of casing 6 5/16 Temp. of water COLD

Diameter and length of casing 6" x 38'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 1½'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4-13-48 Date of completion of well 4-13-48

Type of well rig CABLE TOOL

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	TOP SOIL
6	25	19	SAND AND CLAY
25	30	5	CLAY AND HARD PAN
30	39	9	GRAVEL. WATER.

BAILED DOWN. 8' @ 4/5 G.P.M.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 30' to 39' ft.

Other aquifers
6'-25'

First water at 6' feet.

Casing perforated
from 30 to 37 ft.

Size of perforations
6" x 1/4" x 14 SLOTS.

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 5/8	+1	37.	38	STD. FOL P.Pe. WITH CASE HARD DRIVE SHOE.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

AIR COMPRESSOR 3 HRS 100 G.P.M.
DROW DOWN 10'

J. A. SANGER

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed ..... Well Driller

By .....

License No. 3

Dated 4-19-48, 194.

(Not to be filled in by Driller)

OFFICE STATE ENGINEER