

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **531**  
 Rec. **June 12** 1948  
 Well No. \_\_\_\_\_  
 Permit No. **1155**  
*Do not return*

Owner **R.S. Harmer + Partners at Palms** Driller **S.R. McKinney & Sons**

Address **3075 Cherry Ave. Long Beach, Cal.** Address **Las Vegas, Nev.** Lic. No. **45**

Location of well: **NE SE** 1/4 Sec. **33**, T. **19** N/S, R. **53** E, in **Nye** County

Water will be used for **Irrig. & Domestic** Total depth of well **775 ft.**

Size of drilled hole **10"** Weight of casing per linear foot \_\_\_\_\_

Thickness of casing \_\_\_\_\_ Temp. of water \_\_\_\_\_

Diameter and length of casing **Same as on Log # 267**  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure **150 G.P.M.**

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works **6" Gate Valve**  
 (Type and size of valve, etc.)

**Deeping**  
 Date of commencement of well **April 8, 1948** Date of completion of well **May 11, 1948**

Type of well rig **Bucyrus Erie**

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
			Well drilled by Al Godfrey Lic. # 42 to a depth of 655 ft	
655	696	41	-Cement gravel	Chief aquifer (water-bearing formation) from <b>696</b> to <b>700</b> ft.
696	700	4	Cement Gravel (water)	
700	707	7	gravel	Other aquifers <b>707 to 711</b> <b>725 to 743</b>
707	711	4	gravel ( loose)	
711	725	14	Lime stone	
725	743	18	Gravel- Boulders (water)	
743	775	32	Cement Gravel	
				First water at _____ feet.
				Casing perforated from _____ to _____ ft.
				Size of perforations _____

