

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 662
 Recd. 10/1-1948
 Well No. _____
 Permit No. _____
Do not fill in

Owner E. E. Bouscal Driller Claude R. Keenan
 Address Andover, Nevada Address Winnemucca Lic. No. 13
 Location of well: SE 1/4 SE 1/4 Sec. 3, T. 76 N/8, R. 37 E, in Humboldt County
 or _____
 Water will be used for Domestic & Stock Total depth of well 251'
 Size of drilled hole 6" Weight of casing per linear foot 19.18
 Thickness of casing _____ Temp. of water _____
 Diameter and length of casing 6" x 251'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 178'
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well 9/12/48 Date of completion of well 9/27/48
 Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	55	55	clay gravel & ball clay
55	185	130	cemented gravel
185	205	20	clay & gravel (small amount water)
205	208	3	clay
208	251	43	clay gravel & sand water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 208 to 251 ft.

Other aquifers 205

First water at 205 feet.

Casing perforated from 198 to 251 ft.

Size of perforations

1/8" slots

RECEIVED
 STATE ENGINEER
 OCT 25 1948
 WASHINGTON

