WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 753
Rec. 12/16 1948
Well No.
Permit No.
Do not fill in

Owner John Ansoabehere Driller J B Reynolds
Address Austin Nevada Address Lic. No. 28
Location of well: SE ¼ SW ¼ Sec. 5, T. 24 N/S, R. 44 E, in Lander County
or Three Miles North of Whitakins well
Water will be used for stock water Total depth of well 120'
Size of drilled hole 6" Weight of casing per linear foot Std Pipe.
Thickness of casing 3/8" Temp. of water cold
Diameter and length of casing 6" X 120
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 84'
If flowing well describe control works Wind Mill & stock tanks,
(Type and size of valve, etc.)
Date of commencement of well Sept 20/48 Date of completion of well Sept 29/48
Type of well rig Cable tools,

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	11	11	Silt.
11	8	19	Gravel
19	48	67	Gravel & Clay.
67	5	82	Gravel
82	16	98	Water. sand.
98	22	120	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 82 to 120 ft.
Other aquifers None

First water at 82 feet.

Casing perforated
from 90 to 120 ft.

Size of perforations
¼" X 1½"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailer test. Twenty gals per minute.
This well is on unsurveyed land.
I hope you can find it.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. B. Reynolds
Well Driller

By.....

License No. 28

Dated....., 1948

(Not to be filled in by Driller)