WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 754
Rec. 12/20 1948
Well No.
Permit No.
Do not fill in

Owner: Lyle B. Frey
Driller: Claude R. Keenan
Address: Winnemucca
Address: Winnemucca
Lic. No. 13

Location of well: SW ¼ SE ¼ Sec. 8, T. 43 N/S, R. 37 E, in Humboldt County

or

Water will be used for: Domestic
Total depth of well: 121

Size of drilled hole: 6"
Weight of casing per linear foot: 19.18

Thickness of casing
Temp. of water

Diameter and length of casing: 6" x 121'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 53'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Nov. 15th
Date of completion of well: Nov. 20th

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Burden
4	60	56	clay & gravel
60	72	12	gravel & sand (water)
72	80	8	clay
80	83	3	clay, gravel & boulders
83	121	38	gravel & sand (water)

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 83 to 121 ft.

Other aquifers
60–72
Cased off

First water at 60 feet.

Casing perforated
from 88 to 121 ft.

Size of perforations
1/8" slot

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

35 g.p.m. with no drawdown

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Orlando R. Reeves
Well Driller

By [illegible]

License No. 13

Dated 12/17/, 1948.

(Not to be filled in by Driller)