

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 86  
 Rec. 8/26 1947  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Granite Land & Livestock Co. #6 Driller Warren W. Overholser  
 Address Gerlach, Nevada Address Winnemucca, Nevada Lic. No. 15  
 Location of well: SW 1/4 NE 1/4 Sec. 8., T.34 N/6, R24 E, in Pershing County  
 or 30' off of granite winter road, 3 miles above Simmonds ranch.  
 Water will be used for Abandoned-was for stock. Total depth of well 50'  
 Size of drilled hole 6-3/4 inches Weight of casing per linear foot None  
 Thickness of casing \_\_\_\_\_ Temp. of water \_\_\_\_\_  
 Diameter and length of casing \_\_\_\_\_  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Aug 9, 1947 Date of completion of well Aug 10' 1947  
 Type of well rig Failing Rotary 3I4-G.

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	6'	6'	Sand & brown clay.
6'	10'	4'	Gravel & brown clay.
10'	36'	26'	White to cream clay sulphurish gas, Inflammable.
36'	40'	4'	Total loss of drilling mud water dropped 20'
40'	49'	9'	Very soft blue mud.
49'	50'	1'	Green stinking sulphur mud
coinciding with the same elevation of well #4 which has salty, sulphurous water, and a sweet water well was wanted for pumping for stock use. <u>Abandoned.</u>			

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from None to \_\_\_\_\_ ft.

Other aquifers \_\_\_\_\_  
None.

First water at \_\_\_\_\_ feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

