WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 899
Rec. 6/1 1949
Well No.
Permit No.
Do not fill in

Owner HAMMOND Driller BOWERMAN

Address So VIRGINIA ROAD Address RT1 Box 150 B Reno Lic. No. 29

Location of well: SW ¼ NE ¼ Sec. 17, T. 18 N/S, R. 20 E, in WASHOE County

or On the Christiansen Ranch

Water will be used for Domestic Total depth of well 78'

Size of drilled hole 8" Weight of casing per linear foot

Thickness of casing Standard Pike Temp. of water

Diameter and length of casing 8" — 78'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 4'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 11/14/49 Date of completion of well 11/17/49

Type of well rig Star Rig 71

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20		Fine sand
20	22		Tight dry sand
22	26		" " "
26	27		Coarse gravel
27	42		Sand
42	48		Clay
48	50		Sand & clay
50	65		Sand
65	74		Sand & gravel
74	78		

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 74 to 78 ft.

Other aquifers 26 to 27

First water at 19' feet.

Casing perforated
from 68 to 77 ft.

Size of perforations
4' - 2"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

1500 GPH Quality Good

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By.....

License No. 27

Dated 12/29, 1947

(Not to be filled in by Driller)