WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 912
Rec. 6/1 1949
Well No.
Permit No.
Do not fill in

Owner
Driller John Champion
Address ELKS POINT LAKE TAHOE
Address South Verginiard Reno Lic. No. 29
Location of well: SE¼SE¼ Sec. 16, T. 13 N/S, R 18 E, in Douglas County
or
Water will be used for
Total depth of well 58 FT
Size of drilled hole 12"
Weight of casing per linear foot
Thickness of casing 8 GAGE
Temp. of water
Diameter and length of casing 12" 4 FT LINGATHS
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 8 FT
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well 6/5/48
Date of completion of well 6/10/48
Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	DeComposed GRANITE
48	50	2	SMALL GRAVEL.
50	54	4	CORSE SAND.
54	58	4	LARGE GRANITE GRAVEL.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 54 to 58 ft.
Other aquifers
CORSE SAND.
SMALL GRAVEL.

First water at 4 feet.

Casing perforated
from 48 to 58 ft.

Size of perforations
¼"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12"	0	58	4 ft.	Well is Packed Around outside of Casing with Approx 10 yds of 3/4" Gravel.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed John Champion
Well Driller

By Delbert Bowerman

License No. 29

Dated 6/10, 1948

(Not to be filled in by Driller)