WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

X

Log No. 917
Rec. 6/7 1949
Well No.
Permit No.
Do not fill in

Owner Curtis Cheatman Driller C. C. Moon

Address Black Springs Nev Address 665 West St Lic. No. 75

Location of well: Lot 6 Block C ¼ ¼ Sec. 9, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for Domestic Total depth of well 199

Size of drilled hole 6" Weight of casing per linear foot

Thickness of casing Temp. of water 60°

Diameter and length of casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 135 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 5, 1949 Date of completion of well May 12, 1949

Type of well rig Keystone 50

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	6	4	Volcanic Rock in Clay
6	125	119	Clay with Volcanic Rock
125	133	8	dry Clayish gravel
133	142	9	Clay
142	150	7	Sandy gravel & Silty Clay with Water
150	179	29	Sandy Clay
179	199	20	Sandy Clay with Water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers

First water at 150 feet.

Casing perforated

from 172 to 190 ft.

Size of perforations

3/16 x 6

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well makes about 15 G.P.M.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed C. C. Moore
Well Driller

By.....

License No. 75

Dated June 6, 1949

OFFICE STATE ENGINEER
JUN 7 1949
RECEIVED

(Not to be filled in by Driller)