

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 1055
Rec. 9/6 1949
Well No.
Permit No.

Do not fill in

Owner John W. McCarthy Driller HARVEY MEYER
Address NEW EMPIRE Address CARSON CITY Lic. No. 10
Location of well: NW 1/4, SE 1/4 Sec. 9, T. 15 N/S, R. 20 E, in BRIMBY County

Water will be used for Domestic Total depth of well 60 FEET.

Size of drilled hole 6" Weight of casing per linear foot 12 LBS

Thickness of casing 3/16 Temp. of water 90° F.

Diameter and length of casing 6" - 60'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure No

If nonflowing well give depth of standing water from surface 12 FEET

If flowing well describe control works No
(Type and size of valve, etc.)

Date of commencement of well Aug 26th Date of completion of well 26th

Type of well rig CABLE TOOL S.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	HARD PAN.
2	17	15	SANDY CLAY.
17	20	3	SAND. LITTLE WATER.
20	38	18	SANDY CLAY.
38	47	9	SAND. WATER.
47	57	10	SANDY CLAY.
57	60	3	WATER SAND GRAVEL

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 57 to 60 ft.

Other aquifers

First water at 17 feet.

Casing perforated
from 0 to 24 ft.

Size of perforations
1/8

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL WILL MAKE 1800 G.P.H.
PER HOUR. BATHING TEST

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Meyer
Well Driller

By Harry Meyer

License No. 10

Dated Aug 26, 1947

(Not to be filled in by Driller)

