

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1057  
 Rec. 9/9 1949  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner L.M. Robison Driller C.J. Brackney

Address Fallon Nevada Address P.O. Box 82 Fallon Nev. Lic. No. 16

Location of well: SW 1/4 NW 1/4 Sec. 33, T. 19 N/S, R. 28 E, in Churchill County  
 or \_\_\_\_\_

Water will be used for Domestic purpose Total depth of well 28' 6"

Size of drilled hole 6" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 20 Guage Temp. of water 60%

Diameter and length of casing 6" by 30'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 4 ft.

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 8/18/49 Date of completion of well 8/18/49

Type of well rig Churndrill

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	<u>28' 6"</u>	<u>2' 6"</u>	Sand Loam	Chief aquifer (water-bearing formation) from <u>19</u> to <u>28' 6"</u> ft. Other aquifers <u>4' to 11' 6"</u>  First water at <u>4'</u> feet.  Casing perforated from <u>24</u> to <u>28</u> ft.  Size of perforations <u>1/32/ by 1"</u>
<u>2' 6"</u>	<u>11' 6"</u>	<u>9' 0"</u>	Coarse Sand	
<u>11' 6"</u>	<u>19' 0"</u>	<u>7' 6"</u>	Clay	
<u>19' 0"</u>	<u>28' 6"</u>	<u>9' 6"</u>	Coarse Sand	

