

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1227  
 Rec. 3/2 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Joe Pedro Driller G. J. Brackney  
 Address Fallon, Nevada Address P.O. Box 82 Fallon Lic. No. 6  
 Location of well: N.W. 1/4 S.W. 1/4 Sec. 19, T. 12 N/S, R. 27 E, in Churchill County  
 or \_\_\_\_\_  
 Water will be used for Grade A Barn & Domestic Total depth of well 26"  
 Size of drilled hole 6" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 20 Gauge Temp. of water 58 °  
 Diameter and length of casing 27' by 6"  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 11' 6"  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 2/9/50 Date of completion of well 2/10/50  
 Type of well rig Churn Drill

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
00	10'	10'	Fine sand	Chief aquifer (water-bearing formation)  from <u>21</u> to <u>26</u> ft.  Other aquifers <u>11' 6"</u> to <u>19</u> ft.     First water at <u>11' 6"</u> feet.  Casing perforated from <u>22</u> to <u>26</u> ft.  Size of perforations <u>1/32 / 1</u>
10'	19'	9'	Fine sand	
19'	21'	2'	Clay	
21'	26'	5'	Coarse sand	

