

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1265  
 Rec. 4/4 1950  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner E. J. Ruckleschler Driller Claude R. Keener  
 Address 348 W 3<sup>rd</sup> W. Winnemucca Address W. Winnemucca Lic. No. 13  
 Location of well:  $\frac{1}{4}$  Sec. 30, T. 36N/S, R. 3E, in Humboldt County  
 or In City of Winnemucca  
 Water will be used for Domestic Total depth of well 70'  
 Size of drilled hole 6" Weight of casing per linear foot 19.15 lb  
 Thickness of casing ..... Temp. of water .....  
 Diameter and length of casing 6" x 70'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure .....  
 If nonflowing well give depth of standing water from surface 21'  
 If flowing well describe control works .....  
(Type and size of valve, etc.)  
 Date of commencement of well 3/8/50 Date of completion of well 3/12/50  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	Burden
7	48	41	Sand
48	70	22	Gravel & Sand

Water-bearing Formation, Casing Perforations, Etc.  
 Chief aquifer (water-bearing formation)  
 from 48 to 70 ft.  
 Other aquifers 21'  
 First water at 21' feet.  
 Casing perforated  
 from 50 to 70 ft.  
 Size of perforations  
1/8" slots



