

**WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA**

Log No. 1275  
 Rec. 7/24 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Owner CATHOLIC-CHURCH Driller HARVEY MEYER  
 Address STEWART Address CARSON CITY Lic. No. 10  
 Location of well: NW 1/4 SE 1/4 Sec. 32, T. 15 N/S, R. 20 E, in ORMSBY County

Water will be used for DOMESTIC Total depth of well 90 FEET

Size of drilled hole 6" Weight of casing per linear foot 12 LBS.

Thickness of casing 10-gauge Temp. of water COOL

Diameter and length of casing 6" 85'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure NO

If nonflowing well give depth of standing water from surface 12 FEET

If flowing well describe control works NO  
 (Type and size of valve, etc.)

Date of commencement of well MAR 23 Date of completion of well MAR 27th

Type of well rig CABLE TOOLS

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material
0	6	6	SANDY CLAY
6	9	3	HARD PAN.
9	23	14	SANDY CLAY.
23	28	5	SAND WATER.
28	54	26	SANDY CLAY.
54	85	31	SAND. WATER.
85	90	5	CLAY.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 54 to 85 ft.

Other aquifers \_\_\_\_\_

First water at 23 feet.

Casing perforated

from 0 to 20 ft.

Size of perforations

1/8"

