

**WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA**

Log No. 1277  
 Rec. 4/24 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner JOHN O. KEAR Driller HARVEY MEYER  
 Address NEW AMPIRE Address CARSON CITY Lic. No. 10  
 Location of well: NE 1/4 SW 1/4 Sec. 9, T. 15 N/S, R. 20 E, in ORMSBY County

Water will be used for DOMESTIC Total depth of well 72 FEET

Size of drilled hole 6" Weight of casing per linear foot 12 LBS.

Thickness of casing 10-~~12~~ Temp. of water COOL

Diameter and length of casing 6" — 69' 6"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. NO

If nonflowing well give depth of standing water from surface. 9'

If flowing well describe control works. NO  
(Type and size of valve, etc.)

Date of commencement of well MAR. 28 Date of completion of well MAR 28<sup>th</sup>

Type of well rig CABLE TOOLS

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material
0	4	4	SANDY CLAY.
4	7	3	HARD PAN.
7	12	5	CLAY SANDY
12	15	3	SAND WATER.
15	35	20	CLAY -
35	38	3	SAND WATER.
38	64	24	SANDY BLUE CLAY.
64	72	8	WATER SAND-

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 64 to 72 ft.

Other aquifers \_\_\_\_\_

First water at 12 feet.

Casing perforated

from 0 to 20 ft.

Size of perforations

1/8

