WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1317
Rec. 6/19 1950
Well No.
Permit No.
Do not fill in

Owner: Tony Pecetti
Driller: J. C. Farello & Son
Address: 161½ Mann St. Reno, Nev.
Address: 736 Humboldt St. Reno Lic. No. 2

Location of well: NW¼SE¼ Sec. 6, T. 19 N/S, R 20 E, in Truckee Meadows, Washoe County
or ¼ mile north of Prater Way on Lane by Cramer Auto Court in Sparks, Nev.

Water will be used for: Open Air Theatre
Total depth of well: 67 ft

Size of drilled hole: 6 inch
Weight of casing per linear foot: 19.18 lbs.

Thickness of casing: .280 of an inch
Temp. of water: 58°

Diameter and length of casing: 6" inside diameter, 10'-10" to 11'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 14 ft

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: June 1, 1950
Date of completion of well: June 9, 1950

Type of well rig: Cable Tool Rig, 500 ft, Keystone Type Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Clay soil.
3	5	2	Sand, gravel & rocks with soil.
5	6	1	Sand, gravel & rocks. Little water.
6	10	4	Sand, gravel & rocks with soil. No water.
10	11	1	Sand, gravel & rocks, Water.
11	20	9	Sand, gravel & rocks with soil. No water.
20	25	5	3rd water. Little water. Medium sand. Loose.
25	28	3	4th water. Little water. Fine to medium sand with soil. Loose.
28	33	5	5th water. Water. Fine to coarse sand & coarse gravel, rocks with yellow Loam.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 68 to 70 ft.

Other aquifers: 55 to 63 ft
45 to 47 ft
28 to 33 ft
10 to 11 ft

First water at 5 feet.

Casing perforated
from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
33	37	4	6th water. Little water. Medium sand with yellow loam. Soft.
37	45	8	7th water. Little water. Fine to coarse sand with soil.
45	47	2	8th water. Water. Coarse sand + gravel. Loose. Clean.
47	55	8	9th water. Little water. Yellow clay with fine to coarse sand + gravel. Soft.
55	63	8	10th water. Water. Fine to coarse sand + coarse gravel. Loose.
63	66	3	Yellow clay. Hard. Sticky.
66	68	2	Yellow clay. Soft.
68	70	2	11th water. Water. Fine to coarse sand + coarse gravel. Loose.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0'-06"	65'-01"	65'-07"	Standard black pipe. One screw coupling, one electric welded coupling. Short pattern drive shoe. No perforations.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Big water here. Sand material above 68 ft. is black river bottom sand. Sand material at 68 ft from hills north of well. Pumped and cleaned with air compressor 15 gal. per minute 5 ft drawdown. Water tested safe. Approximate water hardness 31.25 ppm (Lux soap). No turbidity.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Farello & Son
Well Driller

By Harold J. Farello

License No.

Dated June 16, 1950

(Not to be filled in by Driller)