WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1376
Rec. 7/2 1950
Well No.
Permit No.
Do not fill in

Owner: PIERCE BROS. Driller: W S Wright
Address: BAT 99 RANCH DYER NEV Address: Dyer Lic. No. 56
Location of well: SW ¼ SW ¼ Sec 27, T. 3 ~~N~~/S, R 35 E, in ESMERALDA County
or

Water will be used for: NOTHING Total depth of well: 182 FT
Size of drilled hole: 18" To 140 ft 9 in to 182 Weight of casing per linear foot
Thickness of casing: 10 GAUGE Temp. of water: 58
Diameter and length of casing: 14" SET AT 140'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 64'
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: JUNE 14 1950 Date of completion of well: JUNE 20 1950
Type of well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
TOP	8	8	SOIL
8	15	7	SAND
15	72	57	CLAY
72	86	14	GRAVEL
86	140	54	CLAY ROCK & GRAVEL
140	182	42	HARD CONGLOMERATE

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 72 to 86 ft.

Other aquifers

First water at 72 feet.

Casing perforated
from 60 to 140 ft.

Size of perforations
3/16 by 5

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14"	TOP	140'	20'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well Tested 24 Hours with 6" Turbine Pump

Producing 50 gpm.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the ove information is true to my best information and belief.

Signed W S Wright
Well Driller

By W S Wright

License No. 56

ed July 19, 1950

(Not to be filled in by Driller)