

**WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA**

Log No. 1386  
 Rec. 7/31 1950  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Mahoney Driller Louis Clarkson  
 Address Browns New Address Elko Nev Lic. No. 4  
 Location of well: SW 1/4 SE 1/4 Sec. 12, T. 22N/S, R. 48E, in Eureka County  
 or \_\_\_\_\_  
 Water will be used for Stock Total depth of well 75 ft  
 Size of drilled hole 6" Weight of casing per linear foot 19 lbs  
 Thickness of casing 1/4" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6" 75'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 12 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 7-22-50 Date of completion of well 7-26-50  
 Type of well rig Cable tool

**LOG OF FORMATIONS**

| From feet | To feet   | Thickness feet | Type of material         |
|-----------|-----------|----------------|--------------------------|
|           | <u>22</u> |                | <u>yellow clay</u>       |
| <u>22</u> | <u>75</u> | <u>53</u>      | <u>Sand &amp; Gravel</u> |

Water-bearing Formation, Casing Perforations, Etc.  
 Chief aquifer (water-bearing formation)  
 from 22 to 75 ft.  
 Other aquifers \_\_\_\_\_  
 First water at 22 feet.  
 Casing perforated  
 from 26 to 72 ft.  
 Size of perforations  
1/8 x 6"

