


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 1293  
 Rec. 5/1 1960  
 Well No. Basin 4-69  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Dwight G. Vedder Driller A. E. Hosack & Son

Address Paradise Valley, Nevada Address Nampa, Idaho Lic. No. 62

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. 8, T. 39 N/S, R. 32 E, in Humboldt County

Water will be used for Domestic Total depth of well 60'

Size of drilled hole 8" Weight of casing per linear foot 25 lbs.

Thickness of casing 277 Temp. of water 58

Diameter and length of casing 8" - 48' - 0"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 8'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 28, 1960 Date of completion of well May 29, 1960

Type of well rig 72 Stax with Cable tools.

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
C	13	13	Soil
13	47	34	Sand & gravel
47	59	12	Sandy clay
59	60	1	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 13 to 47 ft.

Other aquifers at 60'

First water at 8' feet.

Casing perforated

from 27 to 45 ft.

Size of perforations

3" x 3/16" - torch



