WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1396
Rec. 8/2 1950
Well No.
Permit No.
Do not fill in

Owner Reorganized Silver King Divid Driller J. B. Reynolds
Address Mining Co. Nev. Address Fallon Nev. Lic. No. 28
Location of well: S.E. 1/4 S.W. 1/4 Sec. 10, T. 20 N/S, R. 40 E, in Lander County
or Approx. one mile north east of New Pass Mine
Water will be used for Domestic + Mining Total depth of well 108'
Size of drilled hole 12" Weight of casing per linear foot
Thickness of casing Double 10 gauge Temp. of water Cold
Diameter and length of casing 12" X 108'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure 12 G.P.M.
If nonflowing well give depth of standing water from surface
If flowing well describe control works None
(Type and size of valve, etc.)
Date of commencement of well June 13 - 1950 Date of completion of well June 21 - 1950
Type of well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	69	69	Conglomerate, clay silt gravel, Slide rock encountered. Some water at 15'.
69	76	7	Sand
76	80	4	clay - water gravel water raised to surface
80	108	28	Boulders, gravel, artisian sand + water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 80 to 108 ft.
Other aquifers Small water seepage from 15' to 108'

First water at 15' feet.

Casing perforated
from 80 to 108 ft.

Size of perforations
3/8 x 3"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12	0	108	"	Casing is set on large rocks at Bottom of hole.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. B. Reynolds
Well Driller

By Mrs J. B. Reynolds

License No. 28

Dated July 27, 1950

(Not to be filled in by Driller)