

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1588
 Rec. 19
 Well No. 65
 Permit No. 15670
Do not fill in



Owner Joe Frehner Driller Miller & Allen
 Address Pahrump, Nevada Address 231 Maryland Parkway Lic. No. 40
 Location of well: NE 1/4 NE 1/4 Sec. 9, T21 N/S, R54 E, in Nye County
 or.....
 Water will be used for Domestic & Irrigation Total depth of well 670
 Size of drilled hole 9" Weight of casing per linear foot 14 lb.
 Thickness of casing 14 Gage Temp. of water 72
 Diameter and length of casing 142 ft. of 8" I.D.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Est. 20 G.P.M. / 45.1 ft/ 5/7/51
 If nonflowing well give depth of standing water from surface.....
 If flowing well describe control works 8" Flange and 2" out let 2" valve
 (Type and size of valve, etc.)
 Date of commencement of well Jan. 29, 1951 Date of completion of well March 2, 1951
 Type of well rig 72 Speed Star Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	47	47	brown clay
47	57	10	water bearing gravel
57	67	10	clay & Gravel
67	82	15	course water gravel
82	372	290	Brown clay & Gravel
372	382	10	water sand
382	435	53	clay & Gravel
435	455	20	water sand (Flow)
455	490	35	Brown Clay
490	535	45	Clay & Gravel
535	542	7	Brown Clay
542	547	5	White clay
547	557	10	water sand
557	585	28	Rocks clay & gravel
585	630	45	clay & gravel
630	665	35	sand & gravel
665	670	5	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 435 to 455 ft.

Other aquifers 372 to 382
547 to 557

First water at 47 feet.

Casing perforated
 from to ft.

Size of perforations

