

**WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA**



Log No. 1574
 Rec. 4/23 1951
 Well No. 17
 Permit No. 17110

Do not fill in
 By Mc B. Constant
June 10, 1965

Owner Constant Minerals Driller Mel Meyer

Address Rabbithole, Nev. Address 120 Moana Lane, Reno Lic. No. _____

Location of well: N.E. 1/4 N.W. 1/4 Sec. 33, T. 34 N/S, R. 29 E, in Pershing County _____
 or _____

Water will be used for Mining Total depth of well 340 ft.

Size of drilled hole 6" Weight of casing per linear foot _____

Thickness of casing 65/8" O.D. Temp. of water _____

Diameter and length of casing 6" I.D. 303 ft. 11" casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 19'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 7/28/50 Date of completion of well 8/21/50

Type of well rig _____

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sand, rock, gravel & clay
30	38	8	Gravel, small rocks
38	47	9	Clay, blue shale
47	60	13	Gravel, blue shale
60	75	15	Blue shale
75	77	2	Gravel
77	85	8	Clay, blue shale
85	98	13	Grey shale clay
98	110	12	Small yellow gravel
110	150	40	Clay, blue shale
150	159	9	Gravel
159	198	39	Blue shale, clay, mostly shale
198	228	30	Blue shale clay
228	230	2	Blue shale clay, some gravel
230	240	10	Blue shale clay
240	340	100	Blue shale clay, some gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 98 to 110 ft.

Other aquifers 47'-60' gravel

30'-38' gravel

150'-159' gravel

First water at 33 feet.

Casing perforated from 30 to 159 ft.

Size of perforations

2 1/2" x 3/8"

