LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
				No Casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Indication of Water Very Poor

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed C.A. Bowles
Well Driller

By.....

License No. 100

Dated 4-7, 19 51

(Not to be filled in by Driller)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
140	148	8	Tight Cemented Sand
148	156	8	Clay with Gravel
156	164	6	~~Yellow~~ Clay Coarse Sand
164	204	40	Yellow clay
204	217	13	Coarse Sand
217	219	2	yellow clay
219	223	4	Coarse Sand
223	228	5	Yellow clay
228	233	5	Coarse Sand
233	237	4	Yellow clay
237	239	2	Coarse Sand
239	245	6	Yellow clay

245-248 3 Coarse Sand
245-272 57 yellow clay
272-279 7 Fine Gravel
279-300 21 Yellow clay

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14	0	10	10	#12 Gauge Plain
14	10	100	90	3/16 Plain
14	100	290	190	3/16 Perf 3/16X1 cc
14	290	300	10	#12 Perf 3/16X3 Torch

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Used Estimated 14 Tons 1"&Under Gravel

Test Gal Per Min	Pump level
575	134
540	131
500	126
460	120

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed C. A. Bowman
Well Driller

By

License No. 160

Dated 4-7, 1951

(Not to be filled in by Driller)

Plugged by log #91835