WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1651
Rec. 6/11 1951
Well No.
Permit No.
Do not fill in

Owner John Cavanaugh — Driller E. C. Ferguson
Address Tonopah - Nev — Address Tonopah - Nev Lic. No. 24
Location of well: ¼ ¼ Sec. 9, T. 12 (N)/S, R. 43E, in Nye County
or on old Bill Farrington ranch.
Water will be used for Irrigation — Total depth of well 330 ft
Size of drilled hole 14 in — Weight of casing per linear foot
Thickness of casing 10 gauge — Temp. of water 62°
Diameter and length of casing 14 in - 286 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 60 ft
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well April 10 - 51 — Date of completion of well May 14 - 51
Type of well rig Bucyrus

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Top Soil
4	16 ~~60~~	12	Cement gravel
16	22	6	Loose "
22	60	38	Cement "
60	65	5	Loose "
65	330	265	Cement "

Water-bearing Formation, Casing, Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to 65 ft.
Other aquifers None

First water at 60 feet.

Casing perforated
from 286 to 16 ft.

Size of perforations
5/8 in.

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump test shows poor well for irrigating. Makes app. 300 g.p.m.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed E. C. Ferguson
Well Driller

By D. Ferguson

License No. 24

Dated June 6, 1951

OFFICE STATE ENGINEER JUN 11 51 RECEIVED ANG.

(Not to be filled in by Driller)