Log No. 1662
Rec. 19
Well No. 13507
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner: Earl Crinite
Driller: Rodgers & Smith
Address: Green Shack Las Vegas, Nevada
Address: 8200 Palomino Lane
Lic. No. 31

Location of well: NW ¼ NW ¼ Sec. 1, T. 21 N/S, R. 61 E, in Clark County

or

Water will be used for: Domestic
Total depth of well: 400

Size of drilled hole: 10 Inch. & 8 Inch.
Weight of casing per linear foot: 28 On 8" 16 On 6" 68

Thickness of casing: 5/16 and 5/16
Temp. of water

Diameter and length of casing: 8 Inch. ID 6Inch. ID 80 ft of 8" and 150 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 3/13/51/ 33 G.P.M. /29.7 ft. head

If nonflowing well give depth of standing water from surface

If flowing well describe control works: Cap for pressure Pump
(Type and size of valve, etc.)

Date of commencement of well: February 16, 1951
Date of completion of well: March 3, 1951

Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Sandy Soil
6	10	4	Gravel Sandy Clay Water
10	40	30	White Clay
40	50	10	Gravel Sand Water
50	110	60	Sandy Clay Red
110	115	5	Gravel and Sand Water
115	150	35	Pink Sandy clay layers Gravel and Water
150	170	20	Pink Sandy Clay
170	175	5	Gravel Water
175	370	195	Red Clay some sand
370	375	5	Gravel sand Water
375	400	25	Red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) 370 to 375
from ..... to ..... ft.

Other aquifers 40 to 50
110 to 115

First water at 6 feet.

Casing perforated

from ..... to ..... ft.

Size of perforations

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 OD	0	80	80	This pipe was set for surface well
6 ID	0	150	150	This pipe had a natural shut off of surface water

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well was cemented between 6 and 8 Inch pipe with pure cement

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Rodgers & Smith
Well Driller

By

License No. 31

Dated April 20, 1951

(Not to be filled in by Driller)

VAC 940210:1302
VAC 940210:1302
VAC 439396
VAC 20070103:2998
RUSSELL AVE
FREMONT ST
16201111006
16201111007
16201111008
16201111009
16201111039
16201199039
16201111040
16201111041
16201111019
16201111010
16201111011
16201111012
16201111018
16201111042
16201111020
16201111021
16201111022
16201199031
16201111013
16201111014
16201111015
16201111016
16201111044
16201111026
16201111025
16201111024
16201111023
16201199018
16201199019
130 Feet
GISMO