Copy for State Engr. from Our Files

2 sheets

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1692
Rec. 6/29 1951
Well No.
Permit No.
Do not fill in

Owner R. J. Jennings Motel Stanton Motel - formerly
Address Fernley, Nevada
Driller W. H. Overholser
Address Box 73, Fernley Nev. Lic. No. 15

Location of well: NW ¼ NE ¼ Sec. 14, T. 20 N/S, R. 25 E, in Lyon County
or In The Heart of Fernley.

Water will be used for Industrial + Domestic Total depth of well 42'

Size of drilled hole 16" Weight of casing per linear foot 12#

Thickness of casing 3/32" Temp. of water 60°-7

Diameter and length of casing 6" O.D. 42'-6" 6" above ground
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure no

If nonflowing well give depth of standing water from surface 6'-9"

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well April 22, 1950 Date of completion of well April 25, 1950

Type of well rig Failing Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Fine blow sand
10	20	10	fine sand no silt
20	30	10	fine sand
30	37	7	fine sand, black Mica no silt.
37	41	4	Water washed medium coarse sands and water strata also.
41		1	L Lt yellow Gumbo Clay.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 37 to 41 ft.
Other aquifers 10 - 37'

First water at 10' feet.

Casing perforated
from 38 to 42 ft.

Size of perforations
24 / x 1/8" / x 6" long

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	Plus 6"	42'	42'-6"	gravel packed with 1/4" crushed gravel developed with air compressor, until water was clear and sand free. Casing is 6" O.D. merchant steel pipe threaded & coupled.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Developed to 20 gpm with 40' drawdown, or air hose at that depth. Bottom of casing welded cap and perforations on bottom. Bacteria, not safe at time of sampling, still pumping well.

Total solids 1240
Carbonates 0
Bi-carbonates 472
Sulphates Present
Chlorides 80

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Warren W. Overholser
Well Driller

By MO.

License No.

Dated May 6, 1950

OFFICE STATE ENGINEER JUN 29 '51 RECEIVED AND

(Not to be filled in by Driller)