WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1693
Rec. 7/10 1951
Well No. 25341
Permit No. 13927
Do not fill in 30975-6

Owner Supp Bros Driller A. Bl[illegible]

Address Wells Address Wells Lic. No. 83

Location of well: SE ¼ SE ¼ Sec. 10, T. 37 N/[illegible], R. 61 E, in Elko County

or

Water will be used for Irrigation Total depth of well 170

Size of drilled hole 8 Weight of casing per linear foot 12 gage

Thickness of casing 12 ga Temp. of water

Diameter and length of casing 8"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 88

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well June 10 Date of completion of well June 20

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	92		Rock & Clay
92	107		Water Gravel
107	119		Yellow Clay
119	132		Gravel Water Clay stuck
132	155		Clay & Rocks
155	159		Sand & Gravel Water
154	170		Clay Rocks

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from ..... to ..... ft.

Other aquifers 92 to 107
119 to 132
155 to 159

First water at 92 feet.

Casing perforated

from 90 to 130 ft.

Size of perforations

1/4

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	1	130	130	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pumped 12 hrs And pumped about 500 GPM

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed A. Blanchard
Well Driller

By

License No. 83

Dated July 1, 1957

OFFICE STATE ENGINEER JUL 1957 RECEIVED

(Not to be filled in by Driller)