WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1721
Rec. 8/
Well No.
Permit No. 13413
Do not fill in

Owner: E Flagler
Driller: C. A. Bowker
Address: Big Pine Calif
Address: 271 Western Bakersfield Calif Lic. No. 101
Location of well: NW 1/4 SW 1/4 Sec. 26, T. 3 N/S, R. 35 E, in Esmeralda County
or

Water will be used for: Irrigation
Total depth of well: 246
Size of drilled hole: 19"
Weight of casing per linear foot: 16 gauge
Thickness of casing: 16 gauge
Temp. of water:
Diameter and length of casing: 12" 246
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter)
If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 80 ft
If flowing well describe control works:
(Type and size of valve, etc.)
Date of commencement of well: 5-21-57
Date of completion of well: 7-13-57
Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Soil
5	19	14	Fine sandy clay
19	48	29	Coarse Sand
48	62	17	Fine sand
62	74	12	Grey clay
74	86	12	Fine sand
86	100	14	Grey clay
100	120	20	Streaks of sand & clay
120	131	11	Fine sand
131	134	3	Grey clay
134	146	12	Medium Sand
146	200	54	Sandy Grey Clay
200	246	46	Fine Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 200 to 246 ft.
Other aquifers

First water at 80 feet.

Casing perforated
from 72 to 243 ft.

Size of perforations
1/4 x 100
3" centers

(OVER)

STATE ENGINEER OFFICE

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12	0	246	246	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible]
Well Driller

By.....

License No. [illegible]

Dated 7-18, 1957

OFFICE STATE ENGINEER
AUG 8 57
RECEIVED

(Not to be filled in by Driller)