WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1725
Rec. 8/20 19 51
Well No.
Permit No.
Do not fill in

Owner: Jim Sharp
Driller: E. C. Ferguson
Address: Tonopah Nevada
Address: Tonopah Nev. Lic. No. 24
Location of well: ¼ ¼ Sec. 27 T. 8 (N) S, R. 57 E, in Nye County
or at ranch house
Water will be used for: domestic use
Total depth of well: 220 ft
Size of drilled hole: 6 in
Weight of casing per linear foot:
Thickness of casing: 1/4 inch
Temp. of water: 68°
Diameter and length of casing: 6 in — 175 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 12 ft
If flowing well describe control works:
(Type and size of valve, etc.)
Date of commencement of well: July 13 '51
Date of completion of well: July 29 - '51
Type of well rig: Bucyrus

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	clay
12	24	12	loose gravel
24	50	26	clay
50	60	10	loose "
60	75	15	clay
75	100	25	loose "
100	130	30	clay
130	150	20	loose "
150	200	50	clay
200	210	10	cemented "
210	220	10	gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 210 to 220 ft.
Other aquifers 12-24
50-60, 75-100,
130-150,

First water at 12 feet.

Casing perforated
from 175 to 12 ft.

Size of perforations
1/4 in

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

RECEIVED AUG 20 1951 STATE ENGINEER OFFICE

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed L. C. Ferguson
Well Driller

Log By D. Ferguson

License No. 24

Dated Aug 17, 1951

(Not to be filled in by Driller)