WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1761
Rec. 10/8 1951
Well No.
Permit No.
Do not fill in

Owner: Jack Zolezzi Driller: J.C. Faretto & Son

Address: R1 1 Box 177, Reno, Nevada Address: 736 Humboldt St, Reno Lic. No. 2

Location of well: NE¼NW¼ Sec. 20, T. 18 N/S, R 20 E, in Truckee Meadows, Washoe County or Valley Springs Tract, on Zolezzi lane; ¾ miles west from Reno-Carson Highway

Water will be used for: Domestic Total depth of well: 81'-04"

Size of drilled hole: 6 inch Weight of casing per linear foot: 19, 18 lbs

Thickness of casing: .280 of an inch Temp. of water: 62°

Diameter and length of casing: 6" inside diameter, 4'-08" to 10'-00" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 46'-06"

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: September 19, 1951 Date of completion of well: September 26, 1951

Type of well rig: Cable Tool Rig. 500 ft. Keystone Type Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Pit (5x6x8)
5	20	15	Soil with rocks, gravel & sand.
20	30	10	Yellow soil with fine to coarse sand. Soft.
30	40	10	Yellow soil with fine to a little coarse sand.
40	50	10	Yellow soil with fine to a little coarse sand & a few stones. Soft.
50	53	3	1st water. Water level 45'-06". Little water. Yellow soil, mica & silt with fine to a little coarse sand & some coarse gravel. Loose.
53	56	3	2nd water. Little water. Soil with fine to a little coarse sand, a little gravel.
56	60	4	No water. Soil with fine sand.
60	64	4	3rd water. Little water. Soil with fine to a little coarse sand & a little gravel. Loose.

(OVER)

Plugged by Well log 121010

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 77 to 82 ft.

Other aquifers 68 to 77 ft.
64 to 65 ft.
60 to 64 ft.

First water at 50 feet.

Casing perforated
from 70 to 77 ft.

Size of perforations
3/8" x 3"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
64	65	1	4th water. Water level 43'-08". Little water. Coarse sand, Loose.
65	68	3	Fine sand with yellow soil.
68	77	9	5th water. Little water. Fine to coarse sand, few stones with soil. Loose.
77	82	5	6th water. Little water. Water level 46'-06". Fine to coarse sand and coarse gravel with a little soil. Loose.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	4'-09"	81'-04"	76'-07"	Well drilled in 5'x6'x8' pit. All measurements from ground level. Five lengths of pipe galvanized standard new pipe. Four lengths standard black reconditioned pipe. Welded coupling used. Short patterned drive shoe. Perforations made with acetylene torch 3 slots 1 ft apart.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Sand material granite sand with black sand & some red material. Much [redacted] and silt. Well tested and cleaned with bailer 20 gal. per minute 2'-00" drawd[redacted]n. Approximate water hardness 43.75 ppm (Lux soap). W[redacted]ter has turbidity. Hard water.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated October 4, 1951

(Not to be filled in by Driller)

OFFICE STATE ENGINEER
OCT 5 1951
RECEIVED
ARIZ.