WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1868
Rec. Feb 29 1952
Well No. 679
Permit No. 13710
Do not fill in

West Well Golf Course (Bycle shop) 16939

Owner: Wilbur Clarks Desert Inn. Driller: S.B.Rodgers

Address: Lasvegas Nev. Address: 5200 Palomano Lane Lic. No. 31

Location of well: SE¼ NW¼ Sec. 16, T21 N/S, R63 E, in Clark County

or

Water will be used for: Recreational & Dom. Total depth of well: 450 ft.

Size of drilled hole: 200 Ft. 20 In. 250 16 In. Weight of casing per linear foot: 24 16

Thickness of casing: 3/16 Temp. of water:

Diameter and length of casing: 200 16 275 10 In.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: -11.97 ft

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Oct 3 Date of completion of well: Dec 1 1951

Type of well rig: Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
000	9	9	sand gravel & clay
9	20	11	cement gravel & colechi Watter 12 ft.
20	60	40	brown clay
60	80	140	cement gravel watter
80	190	110	layers pink clay & rock
110	215	105	brown clay & layers rock
215	290	75	cement gravel
290	395	105	layers lavender rock & clay
395	420	25	cement gravel porris Watter
420	30	450	hard Brown rock
			blue clay 450 Finish

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) from 395 to 420 ft.

Other aquifers 12 to 20

195 to 215

First water at 12 feet.

Casing perforated from 150 to 450 ft.

Size of perforations ¼ x 4 in.

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16	000	200	200	cemented with 6 yds. P.G. sand 6 sacks
10	150	250	350	This well was gravelpacked with 20 yards of 3/4" gravel from 150 ft. to 450 ft. around the 10" liner casing to 16" hole.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

This well has not been tested with a pump. However the water droped two feet after the pump on the west well had run for about 4hours.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Cribbs
Well Driller

By S B Rodgers

License No.

Dated Dec 15, 19 51

(Not to be filled in by Driller)