


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 1894
 Rec. 19...
 Well No.
 Permit No. 13271
Do not fill in

Owner William Sherrill Driller Charles Cribbs
 Address Las Vegas, Nevada Address 6200 Palomino Lane Lic. No. 70
 Location of well: SE 1/4 NE 1/4 Sec. 1, T10 N/S, R60 E, in Clark County
 or
 Water will be used for Domestic and Irrigation Total depth of well 506 Ft.
 Size of drilled hole 10" and 14" Weight of casing per linear foot
 Thickness of casing 14" 3/16 10" 3/16 Temp. of water
 Diameter and length of casing 37 Ft. of 14" 90" of 10 inch OD
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 61 3/28/52 - 7.21 M.P.T. of 14" COP
 If flowing well describe control works 0.9 ft above surface
(Type and size of valve, etc.)
 Date of commencement of well January 28, 1952 Date of completion of well March 10, 1952
 Type of well rig Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	2	2	Top Soil	
2	70	68	Caliche	
70	71	1	gravel water	
71	75	4	Caliche	
75	150	75	Sandy clay	
150	200	50	Ledges of sand rock one to three ft. through and making water under each rock	Chief aquifer (water-bearing formation) from <u>150</u> to <u>200</u> ft.
200	280	80	Sandy red clay	Other aquifers <u>315-316</u>
280	315	35	red clay	<u>455-456</u>
315	316	1	gravel and water	
316	455	139	red clay	
455	456	1	water and gravel	
456	500	44	red clay	First water at <u>70</u> feet.
				Casing perforated from to ft.
				Size of perforations



