WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1916
Rec. May 19 1952
Well No.
Permit No. 13549
Do not fill in

Owner John Jay Casey Driller E. C. Ferguson

Address Five Mile Rd - Tonopah Address Bx 202 - Tonopah Lic. No. 24

Location of well: NE ¼ NW ¼ Sec. 32, T. 3 N/S, R 47 E, in MDB&M Nye County

or Flag well - appl # 13549

Water will be used for Cattle Total depth of well 150 ft

Size of drilled hole 6 in Weight of casing per linear foot

Thickness of casing 10 g Temp. of water 52°

Diameter and length of casing 6 in - 150 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 120 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Apr 25-52 Date of completion of well May 1-52

Type of well rig Bucyrus Erie # 30

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Lake Bottom - Hardpan
25	75	50	Coarse Sand
75	115	40	Lake Bottom
115	150	35	Same gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 115 to 150 ft.

Other aquifers

First water at 115 feet.

Casing perforated

from 150 to 100 ft.

Size of perforations

¼ in

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

18 in. Cement plug in bottom

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed E. E. Ferguson
Well Driller

By.....

License No. 24

Dated May 13, 1952

OFFICE STATE ENGINEER
MAY 19 52
RECEIVED

(Not to be filled in by Driller)