WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1945
Rec. June 26 1951
Well No.
Permit No.
Do not fill in

Owner: Tom Smyth — Driller: Glenn McNinch

Address: Imlay, Nevada — Address: Winnemucca, Nev. — Lic. No. 125

Location of well: NW ¼ NE ¼ Sec. 8, T. 32 N, R. 34 E, in Pershing County

or 1 Mile West of Imlay & 1/2 mile north of hwy 40

Water will be used for: domestic — Total depth of well: 81 ft.

Size of drilled hole: 6" — Weight of casing per linear foot: 8.8#

Thickness of casing: 10 gauge — Temp. of water: cold

Diameter and length of casing: 6" inside 81 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 65 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Sept. 5, 1951 — Date of completion of well: Sept. 8, 1951

Type of well rig: Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Top Soil
8	30	22	Hard Pan
30	44	14	Clay
44	67	23	Blue Clay
67	81	14	Sand & Gravel Water Bearing

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
Sand & Gravel
from 67 to 81 ft.

Other aquifers

First water at 67 feet.

Casing perforated
from 61 to 81 ft.

Size of perforations
3 x 1/8

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	81	81	Cement seal

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Glenn McMinch
Well Driller

By.....

License No. 125

Dated June 25th, 1952

OFFICE
STATE ENGINEER
JUN 26 '52
RECEIVED
ANO.

(Not to be filled in by Driller)