

LOCATION INSPECTOR - B.P. SCOTT
 WELL LOG AND REPORT TO THE STATE
 ENGINEER OF NEVADA

Log No. 1988
 Rec. July 12 1952
 Well No. _____
 Permit No. _____
 Do not fill in



Owner William Gregory Driller Joseph J. Harrison

Address Schurz Nevada Address Box 41 Carson City Lic. No. 1

Location of well: $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 36 $\frac{1}{4}$ T. 28 N. 28 E. in Mineral County

or about 1 1/2 miles due east of Schurz Railroad Depot about 120' S. of transformer pole at its home street

Water will be used for _____ Total depth of well 38'

Size of drilled hole 12" Weight of casing per linear foot 5 lbs

Thickness of casing 1/8" Temp. of water Cold

Diameter and length of casing 1 1/8" by 38'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 21'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well July 16-1952 Date of completion of well July 18-1952

Type of well rig Rotary Hydraulic

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Clay, sand, & gravel
25	28	3	Hard pan
28	31	3	sand
31	38	7	coarse sand & gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 28 to 38 ft.

Other aquifers none

First water at 28 feet.

Casing perforated
 from 33 to 38 ft.

Size of perforations
3/16 x 4"

