

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 1999  
 Rec. A49 14 1952  
 Well No. \_\_\_\_\_  
 Permit No. 26654  
*Do not fill in*

Owner ROUND MOUNTAIN GOLD DREDGING CORP Driller CHAMPION PUMP & SUPPLY  
 Address ROUND MOUNTAIN, NEVADA Address RT 1, BX 352 RENO Lic. No. 29  
 Location of well: NE 1/4 NE 1/4 Sec. 20<sup>?</sup>, T. 10 N 8, R. 43 E, in NYE County  
or 300 ft South of A Well #1, approx 9 miles NW from Round Mountain  
 Water will be used for GOLD DREDGING Total depth of well 372 ft  
 Size of drilled hole 16 inch Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 10 ga Red Hard Temp. of water 62°  
 Diameter and length of casing 16" 352 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure NO  
 If nonflowing well give depth of standing water from surface 98 feet  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well 2/28/52 Date of completion of well 7/16/52  
 Type of well rig CABLE TOOL

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	2	2	Sand, Gravel & Clay	130 ft
2	23	21	Sand & Gravel	Chief aquifer (water-bearing formation)
23	68	45	Sand, Gravel & Clay	from 194 to 372 ft.
68	116	48	Gray Sand, Gravel & Clay	Other aquifers _____
116	130	14	Sand & Gravel (WATER)	_____
130	156	26	Cemented Sand & Gravel	_____
156	160	4	Sand & Gravel	_____
160	168	8	Sand & Gravel	_____
168	194	26	Cemented Sand & Gravel (WATER)	_____
194	249	55	Gravel, Sand & Clay	_____
249	282	33	Cemented Gravel & Sand (WATER)	_____
282	284	2	Gravel, Sand & Clay	_____
284	318	34	Gravel, Sand & Clay	First water at 130 feet.
318	335	17	Cemented Gravel & Sand	Casing perforated
335	358	23	Coarse Sand	from 200 to 372 ft.
358	372	14	Gravel & Sand	Size of perforations
				1/4" x 2-1/4"



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"	0	352	352	10 Ga Double Red Hard
12"	276	372	96	10 Ga Single Collared Red Hard overlapping 16" casing from 276 ft to 352 ft with 3 ft 12" x 16" Bell swedged into position.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

started Pumping & Developing Well 7/5/52 Pumped 16 Hrs every day. Finished Pumping 7/16/52. Test started with 625 GPM at 107 ft Pumping Level. Final Result 2000 GPM at pumping Level 130 ft. 62.5 GPM per ft of Drawdown


**WELL DRILLERS STATEMENT**

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed CHAMPION PUMP & SUPPLY  
Well Driller

By John Champion  
License No. 29

Dated AUGUST 12, 1952



(Not to be filled in by Driller)

*RAA by log # 30765*