

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2010 ✓  
 Rec. Aug 18 1952  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Mr. Dodd Driller Mel Meyer  
 Address Ryland Building Reno, Nev. Address 120 Moana Lane Reno, Nev.  
 Location of well:  $\frac{1}{4}$  Sec. 20, T. 19 N/S, R. 19 E, in Washoe County  
 or South Virginia St. and Pine Reno, Nevada  
 Water will be used for Heating Building Total depth of well 124'  
 Size of drilled hole 8" Weight of casing per linear foot 28#  
 Thickness of casing 5/16 Temp. of water Cold  
 Diameter and length of casing 8" id X 123'11"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure .....  
 If nonflowing well give depth of standing water from surface 44'  
 If flowing well describe control works .....  
(Type and size of valve, etc.)  
 Date of commencement of well June 7 - 52 Date of completion of well 6-13-52  
 Type of well rig CABLE TOOLS

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sidewalk and Sand Fill
12	35	23	Red Clay and Rock
35	65	30	Sand Clay Rock
65	72	7	Sand
72	95	23	Gravel and Clay
95	103	8	Clay
103	117	14	Gravel and Clay
117	122	5	Gravel
122	124	2	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 110 to 120' ft.

Other aquifers .....

First water at 44 feet.

Casing perforated from 110 to 120 ft.

Size of perforations

2 1/2 X 3/8



