WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2054
Rec. Sept 28 1952
Well No.
Permit No.
Do not fill in

Owner G. A. Taylor Driller Taylor & Queen

Address Dyer, Nevada Address Box 491. Tonopah Lic. No. 109

Location of well S. E ¼ S. W ¼ Sec. 23, T. 2 N/S, R. 35 E, in Esmeralda Coun

or

Water will be used for Stock & Domestic Total depth of well 90 ft

Size of drilled hole 10½ inches Weight of casing per linear foot 5

Thickness of casing 10 gage Temp. of water ~~58 60~~ 58

Diameter and length of casing 8 inch I. D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Aug 14th Date of completion of well Aug 20th

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	top soil
8	14	6	sand
14	24	10	Clay
24	40	16	Clay with sand & Gravel stratters
40	60	20	sand, Gravel & streaks of Clay
60	72	12	Clay with streaks sand
72	90	18	Sand, Gravel & Clay streaks

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 8 to 90 ft.

Other aquifers

First water at 10 feet.

Casing perforated

from 10 to 80 ft.

Size of perforations

¼ inch slot

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	90'	90'	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the ove information is true to my best information and belief.

Signed Taylor & Queen
Well Driller

By Taylor

License No. 109

ted Sept 12th, 19 52

OFFICE STATE ENGINEER
SEP 29 52
RECEIVED
AUG

(Not to be filled in by Driller)