WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2060
Rec. Oct. 13 195
Well No.
Permit No.
Do not fill in

Owner Ralph Gann Driller H E Hanson

Address Dyer Nevada Address Dyer Nev Lic. No. 113

Location of well: SW¼ SW¼ Sec. 3, T. 2 N/S, R 35 E, in Esmeralda Coun

or

Water will be used for domestic Total depth of well 70

Size of drilled hole 9' Weight of casing per linear foot

Thickness of casing 12 Temp. of water 60

Diameter and length of casing 8" 70'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well July 14-52 Date of completion of well July 25-52

Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Sand & gravel
12	20	8	sandy clay
20	34	14	grey clay
34	70	36	coarse sand & gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 38 to 70 ft.

Other aquifers

First water at 38 feet.

Casing perforated

from 68 to 38' ft.

Size of perforations

1/8 X 1" (Factory)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
174	184	10	Pack sand with clay
184	198	14	Sandy clay
198	220	22	grey clay
220	246	26	Sandy clay & gravel

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14'	0	246	246	used 1" X 6" X 14 shoe (steel) gravel Envelope well 7 mm top to bottom

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Solid not pump well

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the ove information is true to my best information and belief.

Signed H E Hanson
Well Driller

By.....

License No. 113

ted Oct 7, 1952

OFFICE STATE ENGINEER
OCT 1952
RECEIVED

(Not to be filled in by Driller)