

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 2088
 Rec. Nov. 3 1952
 Well No. _____
 Permit No. _____

Do not fill in

Owner Mrs. George Twaddle Jr. Driller J.C. Farutto & Son ✓
 Address Route #2 Box 48, Reno, Nev. Address 736 Humboldt St, Reno Lic. No. 2
 Location of well: NW 1/4 NW 1/4 Sec. 34, T. 20 N, R. 20 E, in Truckee Meadows, Washoe County
or about 1/2 miles north east of Sparks on Spanish Springs Road.
 Water will be used for Domestic Total depth of well 971-03"
 Size of drilled hole 6 inch Weight of casing per linear foot 19.18 b/l.s.
 Thickness of casing .280 of an inch Temp. of water 68°
 Diameter and length of casing 6" inside diameter, 1'-02" to 11'-02"
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 12'-11"
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well October 6, 1952 Date of completion of well October 16, 1952
 Type of well rig Cable Tool Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Clay with fine sand.
10	30	20	Yellow clay with fine to coarse sand.
30	35	5	1st water. Water level 13'-00". Little water. Fine to coarse sand with clay.
35	45	10	2nd water. Little water. Fine sand with yellow soil.
45	55	5	Fine silty sand with soil. Soft & loose.
55	62	7	Clay with fine to coarse sand.
62	70	8	3rd water. Water level 25'-06". Little water. Clay with fine to coarse sand. Soft.
70	75	5	Yellow clay.
75	85	10	4th water. Water level 15'-02". Little

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 30 to 35 ft.

Other aquifers 35 to 45 ft

62 to 70 ft

75 to 80 ft

85 to 90 ft

100 to 107 ft

First water at 30 feet.

Casing perforated

from 58 to 95 ft.

Size of perforations

3/8" x 1 1/2"



