Also See

Log No. 2104 Log. 1905
Rec. Dec. 11 1952
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner: Caliente Public Utilities No. 6 Driller: Darell Free

Address: Caliente Nevada Address: Groche Nevada Lic. No. 30

Location of well: W½ ~~NE~~ SW¼ Sec. 8, T. 4 N/S, R 68 E, in Lincoln County

or

Water will be used for: Culinary Total depth of well: 185

Size of drilled hole: 12 in Weight of casing per linear foot

Thickness of casing: 12 gauge Temp. of water

Diameter and length of casing: 10 to 90 ft. 12 in. 85 to 165 ft. 10 in. 165 to 185 ft. 7 in.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 8 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Nov. 24, 1952 Date of completion of well: Nov. 29, 1952

Type of well rig: Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
See previous well log to 90 ft.			
90	115	25	Stratified sand & clay
115	120	5	Sand
120	145	25	Clay
145	165	20	Sand & gravel
165	185	20	Cemented gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 145 to 165 ft.

Other aquifers: see other log

First water at ..... feet.

Casing perforated

from 90 to 185 ft.

Size of perforations

1/8 x 12 in

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No. 30

Dec 9, 1952

OFFICE STATE ENGINEER
DEC 11 '52
RECEIVED
ANS.

(Not to be filled in by Driller)