


WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Log No. 2116  
 Rec. Jan. 5 19 53  
 Well No.  
 Permit No. 14702  
*Do not fill in*



Owner Rooklidge & Carrado Driller Geo. P. Brooks  
 Address Trona and San Francisco Address Pahrump, Nev. Lic. No. 126  
 Location of well: SE 1/4 SW 1/4 Sec. 6, T. 20 N/S, R. 53 E, in Nye County  
 or S 1/4 cor. of Sec. 6, T. 20 S., R. 53 E., M.D.M.  
 or Bears S. 60 13 E 1180 ft. 53  
 Water will be used for irrigation Total depth of well 200 ft.  
 Size of drilled hole 14 inch Weight of casing per linear foot 35 ft.  
 Thickness of casing 3/16 inches Temp. of water cool  
 Diameter and length of casing 14 in. by 168 ft. depth  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure no flow  
 If nonflowing well give depth of standing water from surface 16 ft. 6 inches  
 If flowing well describe control works none  
 (Type and size of valve, etc.)  
 Date of commencement of well Oct. 6, 1952 Date of completion of well Nov. 2, 1952  
 Type of well rig Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Soil
3	19	16	Soil & Clay
19	23	4	Water sand & clay
23	74	51	clay and caliche
74	77	3	sand & soft clay
77	158	81	Clay & caliche
158	164	6	sand & soft clay
164	200	36	clay, silt, caliche

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 19 to 23 ft.

Other aquifers from 158 - 164  
 main water bearing strata

First water at 19'6" feet.

Casing perforated from 30 ft. to 168 ft.

Size of perforations 3/16 by 4 inches



