WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2129
Rec. Jan 12 1953
Well No.
Permit No. 14479
Do not fill in
Griss Permit.

Owner: Richfield Oil Corp.
Driller: C.R. McKinney & Son
Address: 555 So. Flower St. Los Angeles, Cal.
Address: 1042 So. Main, Las Vegas.
Lic. No. 45
Location of well: NE SW 1/4 NW 1/4 Sec. 26, T. 21 N/S, R. 61 E, in Clark County
or

Water will be used for: Guest-Municipal
Total depth of well: 250
Size of drilled hole: 12" to 60', 8" to 250'
Weight of casing per linear foot: 24 and 20#.
Thickness of casing: 1/4"
Temp. of water
Diameter and length of casing: 8" to 60', 6" to 250'.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 12'
If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Dec. 10, 1952.
Date of completion of well: Dec. 19, 1952.
Type of well rig: Bucyrus-Erie Spudder.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Surface soil&gravel
5	12	7	Hard cemented gravel
12	26	14	White clay
26	28	2	" "
28	34	6	Rock (caliche)
34	41	7	White clay
41	46	5	Rock (caliche)
46	56	10	White clay
56	58	2	Rock (caliche)
58	78	20	White clay
78	82	4	Rock(caliche)
82	95	13	White clay
95	99	4	Rock(Cement gravel) Water.
99	135	36	Brown clay
135	141	6	Rock (cement gravel) Water.
141	185	44	Red clay
185	190	5	Rock(limestone)
190	230	40	Red clay
230	236	6	Gravel, Water.
236	240	4	Red clay
240	244	4	Gravel, Water.
244	250	6	Red clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 230 to 236 ft.
~~236 240-244~~
Other aquifers
95-99. 135-141.

First water at 12 feet.

Casing perforated
from 114 to 250 ft.

Size of perforations
30 mesh

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"I.D.	0	60	60	Cemented with 40 sacks.
6"I.D.	0	250	250	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailing test at 200 Ft., 30 gpm, draw down to 55 ft.

" " " " 250 " 35 " " " " 30 ".

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed S. R. McKinney & Son
Well Driller

By S. R. McKinney

License No. 45

Dated Dec 24, 1952

(Not to be filled in by Driller)